

WAAS CH <b>61103</b> <b>W27A</b>	APP CRS <b>270°</b>	Rwy Idg TDZE Apt Elev	<b>5998</b> <b>92</b> <b>112</b>
--	------------------------	-----------------------------	--

# RNAV (GPS) RWY 27

ESLER RGNL (E/SF)

RNP APCH-GPS.

**⚠** Circling Rwy 14, 32 NA at night. Baro-VNAV and VDP NA when using Alexandria Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C or above 54°C. When local altimeter setting not received, use Alexandria Intl altimeter setting: increase LPV DA to 327 feet; increase LNAV/VNAV DA to 457 feet and all visibility 1/8 SM; increase all MDAs 40 feet and LNAV visibility Cat C/D 1/8 SM and Circling visibility Cat D 1/4 SM. For inop MALSRS increase LNAV/VNAV all Cats visibility to 1 mile and LNAV Cat C/D visibility to 1 1/8. For inop MALSRS, when using Alexandria Intl altimeter setting, increase LNAV/VNAV all Cats visibility to 1 SM.

MALSRS




**MISSED APPROACH:**  
Climb to 3000 direct HOVUS and on track 214° to AEX VORTAC and hold.

ESF ASOS  
**119.425**

POLK APP CON  
**125.4 254.8**



UNICOM  
**122.8** (CTAF) **①**



SC-4, 22 FEB 2024 to 21 MAR 2024

SC-4, 22 FEB 2024 to 21 MAR 2024

ELEV 112	TDZE 92
----------	---------



CATEGORY	A	B	C	D
LPV DA		292-1/2	200 (200-1/2)	
LNAV/VNAV DA		422-1/2	330 (400-1/2)	
LNAV MDA	500-1/2	408 (400-1/2)	500-3/4	408 (400-3/4)
CIRCLING	600-1	488 (500-1)	740-1 3/4 628 (700-1 3/4)	760-2 648 (700-2)

REIL Rws 9, 14 and 32 **①**  
MIRL Rwy 14-32 **①**  
HIRL Rwy 9-27 **①**