


WAAS CH 82699 W11A	APP CRS 123°	Rwy Idg TDZE Apt Elev	9000 618 618
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 11
ST LOUIS LAMBERT INTL (STL)

RNP APCH. ▼ Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 4000 and LNAV Cat E visibility to 1¼ SM.		ALS F-2 ⓐ	MISSED APPROACH: Climb to 3000 direct YOBUC and on track 195° to IMPER and hold.		
D-ATIS 125.025 379.925	ST. LOUIS APP CON 132.125 360.6	ST. LOUIS TOWER 132.475 239.275	GND CON 121.9 348.6 (Inbound) 121.65 377.175 (Outbound) 118.925 227.125 (Rwy 11/29)	CLNC DEL 119.5 363.1	CPDLC



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 67°).						3000	YOBUC	tr 195°	IMPER
SISDE						5000	HILPI	JEXAR	RW11
GP 3.00° TCH 55						3500	2500	2500	1.1
4.4 NM						6 NM	4.5 NM	1.1	
CATEGORY	A	B	C	D	E				
LPV DA	868/18 250 (300-½)								
LNAV/VNAV DA	960/40 342 (400-¾)								
LNAV MDA	1040/24	422 (500-½)	1040/40 422 (500-¾)	1040/50	422 (500-1)				
						HIRL all Rwys TDZ/CL Rwys 11, 12L, 12R, 29, and 30R			

NC-3, 22 FEB 2024 to 21 MAR 2024

NC-3, 22 FEB 2024 to 21 MAR 2024